


**R-1009-40-R C40 REMOVABLE CRASH-RATED BOLLARD
SINGLE STAND ALONE, UNRESTRICTED SPACING, SET AND POUR FEATURE**

ENGINEERED & DESIGNED FOR C40, P1 (CRASH TESTED PROTOCOL) PROPERLY INSTALLED, STOPPED 2430 lbs PASSENGER CAR AT 40MPH OR STOREFRONT EQUIVALENT ASTM F2656


**SINGLE STAND ALONE BOLLARD
INSTALLATION**

FRONT VIEW



NOTE:
REMOVABLE BOLLARD
MODEL IS AVAILABLE
WHICH USES THE SAME COMPONENTS.

TOP VIEW



KEY CAPABILITIES:

1. UNRESTRICTED SPACING BETWEEN BOLLARDS
2. EASY AND QUICK INSTALLATION; EXCAVATE SET BOLLARD AND POUR CONCRETE
3. NO FIELD WELDING, BOLTING OR ASSEMBLY. BOLLARD IS DELIVERED PREFABRICATED AS 1 UNIT
4. SYMMETRICAL BOLLARD DESIGN, IMPACT FROM ANY ANGLE TO BOLLARD PROVIDES THE SAME STOPPING CAPABILITY

Developed By

RELIANCE FOUNDRY
SINCE 1925

THIS PLAN DRAWING AND DESIGN ARE, AND AT ALL TIMES REMAIN, THE EXCLUSIVE PROPERTY OF RELIANCE FOUNDRY CO. LTD.

**DETAILS
ASTM F2656 C40 PROTOCOL
SET & POUR BOLLARD**

DRAWINGS

SHEET: 1 OF 5

20190603-01-PD

SCALE: N.T.S.